

OPTIO 58BW FLUSH WINDOW CONTENT

Combining minimal sight lines with maximum durability & weather resistance.

Perfect for a range of new build or refurbishment projects, the 58BW flush window offers a sleek flush finish and advanced functionality. With a choice of window configurations and slim sashes, the 58BW can achieve stunning aesthetics without compromising on the exceptional standards of weather protection, security and durability.


DESIGN FEATURES

- Certified under the Secured By Design scheme
- Tested to PAS 24
- Features integrated deep head profiles for ease of trickle ventilation
- A polyamide thermal break design to improve thermal performance

OPTIONS

- Glazing 24mm 40mm
- Internally or externally glazed
- Available in a selection of single or dual colours, as well as anodised finishes
- Available in flush, bay, chamfered, heritage, ovolo and contemporary aesthetics
- 70mm frame depth
- Available in a range of configurations: top hung, bottom hung, side hung, fixed light, multi-light and French casement






SPECIFICATIONS

PERFORMANCE ANI	O ACCREDITATION
U-Value (Double Glazing) (Ug: 1.0 W/m2K)	1.5 W/m²K
Window Energy Rating (WER)	B-C
Air Permeability	Class 4 (600 Pa)
Water Tightness	Class 9a (600 Pa)
Wind Resistance	Class E2400 (2400 Pa)
Acoustic Performance	Rw (C;Ctr) 42 (-1;-5) dB
Security	PAS 24 & SBD
3rd Party Certification Q-Mark	✓
SYSTEM	
Depth	70mm
CONFIGURATIONS	

Depth	70mm
CONFIGURATIONS	
Top Hung	✓
Side Hung	✓
Dummy Sashes	✓
Multi-Light	✓
French Casement	✓

Jamb Section




-	
74	94
53 , 15	73 15
S3 15 AM463 P R R R R R R R R R R R R R R R R R R	104-033 AW-055 AW-055 AW-055 10

SIZE AND WEIGHT	LIMITS
Top Hung	
Max. size (mm)	1400w x 1200h
Min. size (mm)	350w x 250h
Max. Weight	35kg
Side Hung	
Max. size (mm)	700w x 1400h
Min. size (mm)	300w x 350h
Max. Weight	26kg
Bottom Hung	
Max. Weight	50kg (2 hinges)
Fixed Light	
Max. Weight	250kg
SYSTEM FEATURES	
Single Colour	✓
Dual Colour	✓
Textured Finish	✓
Anodised Finish	✓
Multi-Point Locking	✓
SIGHTLINES	
Frame to Vent	74mm
Vent to Mullion to Vent	111mm
Dummy Sash	74mm
GLAZING	
Glazing Options	Internal Bead

French Casement Floating Mullion

24mm - 35mm

Glazing Thickness



U-Value (Double Glazing) - Windows are calculated using EN ISO 10077 - Part 2, 1230mm x 1480mm Side hung next to fixed light with Ug: 1.0 W/m²K using AW603 outerframe and AW614 ventU-Value (Triple Glazing) - Windows are calculated using EN ISO 10077 - Part 2, 1230mm x 1480mm Side hung next to fixed light with Ug: 0.7 W/m²K using AW603 outerframe and AW685 vent

Green Guide Rating - Calculated using the Green Guide 2008 ratings for domestic windows, Powder Coated Aluminium window (Profile <0.88kg/m) double glazed Acoustic Performance (dB) - Tested using AW604 outerframe and AW685 vent, 8/16/8.8mm Acoustic Laminated Glass

Top Hung (max weight) - Based upon Nico 24" Standard top hung friction stay / Side Hung (max weight) - Based upon Nico 16" Standard side hung friction stay / Bottom Hung (max weight) - Based upon 3 x RW20M hinges









Glass & Glazina Federation Member

Arkay Windows is a specialist large-scale fabricator *with over 30 years experience* based in Watford, North West London.

Through growth built on putting our customers first, we have risen to supply some of the country's biggest retail companies, contractors and commercial installers.

Arkay Windows

Watford: 01923 803923 London: 020 8889 6821

58BW@arkaywindows.com

www.arkaywindows.com

